

HEAVY DUTY STRIPPER

Quickly penetrates through layers of old finish and wax and dissolves them for easy removal. Works on all kinds of floors; asphalt, rubber, vinyl asbestos, vinyl and clay tiles, linoleum, terrazzo and marble.

HARD WORKING FORMULA

Softens buildup of floor finish films, destroys the chemical bonding structure and emulsifies the fold finish for easy removal. This stripper keeps on working where other strippers leave off.

EVAPORATION CONTROL

Stripper's controlled evaporation ingredients hold old finishes on surface longer to help prevent re-depositing and drying.

SUPER CONCENTRATED

Economy. Can be diluted with 5 parts of water for stripping heavy buildup and up to 1 to 40 for light stripping.

Specially designed to remove today's high solids polymer finishes.

DESCRIPTION

This stripper is especially formulated to remove all types of floor waxes and finishes from all kinds of floors. It works in a new way to penetrate quickly the most stubborn wax and polymer finish films so they can be removed more readily.

APPLICATION

For use on all types of floors including: Asphalt, Concrete, Marble, Quarry tile, Stone, Rubber, Terrazzo, Vinyl, Vinyl Asbestos, Ceramic tile.

DIRECTIONS FOR USE

Mix STRIPPER with warm (not hot) water. Hard water will not hamper stripper. Use the following dilutions (expressed as 1 part STRIPPER to x parts of water): 1 to 2 - For floors that have been badly neglected. 1 to - For non-buff able, metal cross-linked polymer finishes or for very heavy buildup of finishes (1 gal of mix for 250 sq ft of floor). 1 to 10 - For buff able waxes and water-resistant waxes. 1 to 20—For non-water resistant waxes. 1 to 40 - for new, previously unfinished floors to remove oily coatings placed there by the manufacturer. • Soak (do not flood) an area not over 10 x 20 ft., and let stand for 5-10 minutes. • Seal old or porous floor with a floor sealer before refinishing floor.

SPECIFICATIONS

Packaged: Drums, 5- gallon Enviro-pak, 4- 1 gallons
 Appearance: Clear liquid
 Odor:Ammoniacal
 pH:3.00
 Flash point:None. Non-flammable
 Solubility in water:Complete

P.O. Box 603207, Cleveland, OH 44103 * 216-566-9858 * 800-426-5820 * Fax: 216-566-1228
www.kaylinecompany.com

**Let Kayline Service All Your
Building Maintenance Product Requirements!**

Industrial Cleaners □ Disinfectants □ Deodorizers □ Floor Finishes □
 Housekeeping Cleaners □ Hand Soaps □ Insecticides □ Weed Killers □
 Sewer & Drain Maintenance □ Winter Products □ Water Treatment □
 Roofing, Driveway, Flooring □ Long Life Light Bulbs □ Incandescent □
 Fluorescent □ Decorative □ Mercury Vapor □ Metal Halide □ High
 Pressure Sodium □ Quartz Halogen □ Compact Fluorescents □ Energy
 Saving Conversions □ Ballasts □ Specialty Lamps