



K198 URETHANE CONCRETE SEAL

DESCRIPTION:

An economical oil modified urethane concrete sealer designed to combine full gloss with tough durability. Outstanding leveling characteristics produce a uniform film that is highly resistant to chemicals, abrasion and is unsurpassed for resistance to rubber burns.

PRODUCT CHARACTERISTICS:

- Easily applied - ready to use, no mixing
- Provides a hard, long lasting finish
- Prevents dusting, crumbling, and erosion of concrete
- Extends floor life - high abrasion and impact resistance
- Excellent resistance to alcohol, alkali, fumes, gases, grease, oil, gasoline, ink, citrus juices, cleaning chemicals, moisture and rubber burns
- Reduces down time - area can be opened for traffic 24 hours after final coat
- Extra light color will not discolor floor or yellow with age
- High gloss for increased light reflection
- Cuts maintenance costs - prevents soil penetration so cleanup is fast and thorough
- 40% solid contents

RECOMMENDED USE:

This product is intended for use as both an initial seal and subsequent finish coat on factory warehouse, garage or other industrial and institutional concrete floors.

USDA AUTHORIZED FOR USE IN FEDERALLY INSPECTED MEAT & POULTRY PLANTS

COVERAGE:

First Coat	300-400 square feet per gallon
Additional Coats	400-500 square feet per gallon

DRY TIME:

To Touch	2 hours
Hard	4-8 hours
Open To Traffic	24 hours
Between Coats	12-24 hours
Full Cure	7 days