K202 SEAL PRO K202A SEAL PRO - ALMOND K202B SEAL PRO - BLACK K202W SEAL PRO - WHITE

# MATERIAL SAFETY DATA SHEET

100% RTV Silicone - Standard Acetoxy

Manufactured by: Adaseal International Inc P O BOX 377

NEW JOHNSONVILLE, TN 37134 EMERGENCY PHONE: 800-521-2521

CHEMTREC: 800-424-9300

#### PRODUCT IDENTIFICATION

Product Identification: 100% RTV Silicone: clear, white, black, blue, bronze, aluminum, red, trans white, almond, grey, biscuit, light grey, snowy white

Chemical Name: Silicone Sealant Chemical Family: Silicone Sealant

Formula: Mixture

## PRODUCT COMPONENTS

|    | COMPONENT                             | CAS#                    | WT% EXPOSURE LIMITS |   |  |  |
|----|---------------------------------------|-------------------------|---------------------|---|--|--|
|    | Dimethyl siloxane, hydroxy-           |                         |                     |   |  |  |
|    | terminated                            | 70131-67-8              | > 60.0              |   |  |  |
|    |                                       |                         |                     |   |  |  |
|    | Silica, amorphous                     | 7631-86-9               | 7.0 - 13.0          |   |  |  |
|    |                                       |                         |                     |   |  |  |
|    | Hydrotreated middle petroleum         |                         |                     |   |  |  |
|    | distillates                           | 64742-46-7              | <= 7.0              | OSHA PEL (final rule) and AC 5 mg/m3      | OSHA PEL (final rule) and ACGIH TLV for oil mists: TWA 5 mg/m3 |  |
|    | Ethyltriacetoxysilane*                | 17689-77-9              | 1.0 - 5.0           | See acetic acid comments.                 |  |  |
|    | Methyltriacetoxysilane*               | 4253-34-3               | 1.0 - 5.0           | See acetic acid comments.                 |  |  |
|    | Difluoroethane**                      | 75-37-6                 | 1.0 - 5.0           | See aerosol product comments              |  |  |
| nı | nents: *Acetic acid is formed upon co | intact with water or hu | mid air Drovi       | de adequate ventilation to control exposi | ures within guidelines of OSHA DEL TWA                         |  |

\*Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA

## PHYSICAL AND CHEMICAL PROPERTIES

Physical form: Paste

Color: Depends on specific color ordered,

Odor: Acetic acid odor

Specific Gravity @ 25c: 1.007

Viscosity: Not determined

Freezing/Melting Point: Not determined Boiling Point: Not determined Vapor Pressure @ 25c: Not determined Vapor Density: Not determined Solubility in Water: Not determined

pH: Not determined

Volatile Content: Not determined

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

## FIRE AND EXPLOSION DATA

Flash Point (Closed Cup):

> 212°F / > 100°C

Autoignition:

Not determined

Flammability Limits in Air:

Not determined

Extinguishing Media:

Carbon Dioxide (CO2), Water, Water fog (or spray) Dry Chemical Foam

Unsuitable Extinguishing Media:

Fire Fighting Procedures:

Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

If large amount is involved, evacuate area.

Unusual Fire Hazards:

None.

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Sulfur Oxides. Carbon oxides and traces of incompletely burned carbon compounds.

Silicon dioxide. Iodine compounds. Formaldehyde.

If container is an aerosol product: DO NOT remove rubber plug from bottom of container. Treat as compressed gas: extinguishing media- CO2, Dry Chemical, Water Fog.

<sup>\*\*</sup>If container is an aerosol product: Propellant remains in can during and after normal use and is not expelled with product. DO NOT remove rubber plug from bottom of container.

K202 SEAL PRO K202A SEAL PRO - ALMOND K202B SEAL PRO - BLACK K202W SEAL PRO - WHITE

#### 5. REACTIVITY DATA

Stability: Stable

Incompatibility (material to avoid): Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form.

Conditions to Avoid: None

Hazardous Decomposition Products: Carbon oxides and traces of incompletely burned carbon compounds, silicon dioxide and formaldehyde.

Hazardous Polymerization: Will not occur.

#### 6. HEALTH HAZARD DATA

Acute signs/effects of overexposure:

Ingestion: May cause gastric distress.

Skin contact: Uncured product contact will irritate lips, gums, tongue and skin.

Inhalation: Causes mild respiratory irritation.
Eye contact: Uncured product contact irritates eyes.
Medical conditions aggravated: None known
Other: Acetic acid released during curing.
Chronic effects of overexposure: None known

Emergency first aid procedures:

Ingestion: No first aid should be needed.

Skin: To clean from skin, remove completely with a dry cloth or paper towel before washing with detergent

and water. Get medical attention if irritation develops.

Inhalation: Remove to fresh air.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention.

Note to physician: None known.

Toxicity:\*\*Product Information Acute Oral LD50>10,000 MG?KG Other: None known. Ames test: Unknown

Acute dermal LD50 None found MG/KG Acute Inhalation LC50 None found.

Principle routes of exposure: Eyes, Inhalation

Products/Ingredients: None known

## 7. SPECIAL PROTECTIVE EQUIPMENT

Respiratory Protection: Use in a well ventilated area.

Protective Gloves: Cloth gloves Eye and Face Protection: Safety glasses Other Protective Equipment: None known Ventilation: Use only in well ventilated area.

## 8. SPILL, LEAK, AND DISPOSAL PROCEDURES

Action to be taken if material is released or spilled: Wipe or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

Disposal Method: Disposal should be made in accordance with Federal, State, and Local Regulations.

## 9. SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Avoid contact with skin and eyes. CAUTION! Wearers of contact lenses must not handle lenses until all sealant has been cleaned from fingertips; residual silicone will transfer to lenses and cause severe eye irritation.

Products releases acetic acid during application and curing.

Use mechanical ventilation to stay below TLV of 10 PPM acetic acid.

Uncured product contact irritates eyes. Uncured product contact irritates skin.

Use in a well ventilate area to prevent irritation by vapors.

Engineering Controls: Eye wash stations

VOC Content is 31 grams per liter

#### 10. SHIPPING AND REGULATORY CLASSIFICATION DATA

DOT Shipping Name: None
DOT Hazard Class: None
DOT Label(s): None
EPA Hazard Class: Eye irritant
CPSC Classification: Eye irritant

CPSC Classification: Eye irritant Transportation Class: IMO None

RID(OCTI) None ADR (ECE) None RAR (IATA) None

NEPA/HMIS Classification: Flammability 1, Reactivity 0, Health 1

Additional information: These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is made. The recommended handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use.

All material has a 1year shelf life from the date stenciled on the product. Rev 01/31/2019

Distributed By: